

MINI HEAD

**Portable
Disintegrator
Head**



The lightweight, compact Mini DC disintegrating head is designed to remove broken tooling from #2 to 3/4" (2 mm to 19.05 mm) in a single pass. Overall length 8.25" (209 mm). Operates at any angle. A straight arbor 1/2" diameter x 2.75" long (12.7 x 70 mm) allows mounting this general purpose head in magnetic fixtures and other machine tools. A special power coolant cable delivers the disintegrating power and coolant to the head. Part #S-270



**REMOVE
BROKEN TAPS
BOLTS & DRILLS
IN MINUTES**

PERFORMANCE

BROKEN TOOLING ONE INCH DEEP	REMOVAL TIME
0-80 to 10-32 No. 1.6	UNDER 1 min.
1/4" No. 6	1 - 2 min.
5/16" No. 8	1.5 - 2.5 min.
3/8" No. 10	1.5 - 2 min.
1/2" No. 14	2 - 4 min.
5/8" No. 18	1.5 - 2.5 min.
3/4" No. 22	2.5 - 3.5 min.



**Mini magnetic 800-lb. (362.8 kg) base
with fixture for Mini Head (optional)**

800 lb. permanent magnet holds firmly to all ferrous surfaces. Enables precise manual feed. Part # A1425

Vacuum-base version Part #A1426