

# Molybdenum tubing

## Available sizes

Part Number	Outside Diameter	O.D. Tolerance	Inside Diameters	I.D. Tolerance	Maximum Length
1604-RL	0.040	-0.002/+0	0.024	-0.002/+0	48"
1605-RL	0.050	-0.002/+0	0.030	-0.002/+0	48"
1606-RL	0.060	-0.002/+0	0.036	-0.002/+0	60"
1607-RL	0.075	-0.002/+0	0.045	-0.002/+0	60"
1608-RL	0.079	-0.002/+0	0.049	-0.002/+0	60"
1609-RL	0.090	-0.002/+0	0.054	-0.002/+0	60"
1610-RL	0.098	-0.002/+0	0.062	-0.002/+0	60"
1611-RL	0.110	-0.002/+0	0.066	-0.002/+0	60"
1612-RL	0.118	-0.002/+0	0.068	-0.002/+0	72"
1613-RL	0.125	-0.002/+0	0.074	-0.002/+0	72"
1613-RLS	0.125	-0.002/+1	0.094	-0.002/+1	60"
1613-SID	0.125	-0.002/+2	0.070	-0.002/+2	48"
1614-RL	0.140	-0.002/+0	0.084	-0.002/+0	72"
1615-RL	0.156	-0.002/+0	0.093	-0.002/+0	72"
1617-RL	0.170	-0.002/+0	0.102	-0.002/+0	60"
1618-RL	0.177	-0.002/+0	0.102	-0.002/+0	60"
1619-RL	0.187	-0.002/+0	0.112	-0.002/+0	60"
1619-RLS	0.187	-0.002/+1	0.140	-0.002/+1	36"
1620-RL	0.200	-0.002/+0	0.120	-0.002/+0	48"
1622-RL	0.218	-0.002/+0	0.132	-0.002/+0	48"
1623-RL	0.230	-0.002/+0	0.140	-0.002/+0	48"
1624-RL	0.236	-0.002/+0	0.145	-0.002/+0	60"
1625-RL	0.250	-0.002/+0	0.150	-0.002/+0	60"
1627-RL	0.277	-0.002/+0	0.161	-0.002/+0	36"
1629-RL	0.290	-0.002/+0	0.176	-0.002/+0	36"
1631-RL	0.312	-0.002/+0	0.187	-0.002/+0	36"

V0216