



# METAL DISINTEGRATORS

## EXTRACTALL X2

The COMPACT DC disintegrator system for serious service jobs

Compact and portable.

Salvage parts without damage in minutes.

Removes taps from #2 (2 mm) up to 3/4" (19.05 mm) in one pass.

125 lb. power supply. Take it anywhere.

Quick connections on all cables.

110V AC input is all you need.

Fast cutting action in HSS and carbide.

Compact, lightweight disintegrating head.

Straight shank arbor for drill press use.

Magnetic fixtures available.



**REMOVE  
BROKEN TAPS  
BOLTS & DRILLS  
IN MINUTES**

### PERFORMANCE

BROKEN TOOLING ONE INCH DEEP	REMOVAL TIME
0-80 to 10-32 No. 1.6	UNDER 1 min.
1/4" No. 6	1 - 2 min.
5/16" No. 8	1.5 - 2.5 min.
3/8" No. 10	1.5 - 2 min.
1/2" No. 14	2 - 4 min.
5/8" No. 18	1.5 - 2.5 min.
3/4" No. 22	2.5 - 3.5 min.



### OPTIONAL Mini Mag Head Support Fixture

The ideal way to bring disintegrating power to bear at ANY angle. 800 lb.- force permanent magnet. 6 precision angle/position adjustments. 5" (127 mm) vertical, 4.5" (114 mm) horizontal movement. 4" (101 mm) of downfeed. Part # A1425



# Model X-2

## SPECIFICATIONS

<b>OPERATING HEAD</b>	Operating head with 2.5" x 0.5" (63 x 13 mm) shank for chucking into machine shop tools. Vibrating head creates 120 cutting arcs per second.
<b>POWER SUPPLY</b>	Stainless steel cabinet 24" wide x 12.5" deep x 15.25" high (604 x 317 x 387 mm). Hinged locking cover. Fold-down handle on each end. Ten foot (3 m) 110 volt AC input cable. 30 amps required. Controls include start, stop, yellow ON indicator, heat selector with eleven selections, coolant on/off switch, vibration control, current meter and power overload circuit breaker. Receptacles for power, ground, pump and head vibration cables.
<b>CABLES</b>	Work Cable: Copper welding cable with jack plug. Head Cable: Copper welding cable with jack plug and encapsulated head vibration power cables. Both 10 ft (3 m).
<b>COOLANT SYSTEM</b>	Standalone coolant pump and motor (110 V AC). 1/3 HP pump provides 90 PSI to head from coolant tank or bucket (not included). Coolant can be recycled if provision is made to collect runoff from the workpiece. Two 10 ft (3 m) coolant hoses with quick disconnects.
<b>SHIPPING DATA</b>	Weight: Net 150 lb (68 kg), gross domestic 225 lb (102 kg). Volume: 8 cu ft (0.227 M)

## OPTIONS


V1019

### Build your complete mobile disintegration station



### Accessory Basket

For head, cables, accessories. Rubber coated heavy wire construction. Part No. S-204



### Cabling options

20 foot Power Cable	Part #S-220
20 foot Ground Cable	Part #S-221
Head Cord Extension 10 ft	Part #S-212

### Coolant Tank

16-gallon durable frosted plastic resists corrosion. Built-in filter, barbed fitting for quick disconnect. Large screw-on fill cap with pressure relief valve. Fits perfectly on lower deck of the cart. Part No. S-203



### Stainless Steel Cart

Welded joints and handle. Room below for coolant tank and extras. Heavy-duty lockable wheels; back pair are casters. Dimensions: 30" x 60" (762 x 1524 mm) footprint. Height: 37" (939.8 mm) to top of handle, 27" (686 mm) to top shelf.

Part No. S-202

### Coolant Valve

Offers dual coolant sources: tank or garden hose.

Part No. A6448



**ELECTRO ARC MANUFACTURING COMPANY** *STILLION INDUSTRIES*

USA  
Phone: (734) 475-8527  
Fax: (734) 475-2902  
sales@electroarc.com

www.electroarc.com



UK  
Phone +44 (0) 1384 231535  
Fax: +44 (0) 1384 252834  
sales@electroarc.co.uk