



METAL DISINTEGRATORS

EXTRACTALL X2

The **COMPACT**
DC disintegrator system
for serious service jobs

Compact and portable.

Salvage parts without damage in minutes.

Removes taps from #2 (2 mm) up to
3/4" (19.05 mm) in one pass.

125 lb. power supply.
Take it anywhere.

Quick connections on all cables.

110V AC input is all you need.

Fast cutting action in HSS and
carbide.

Compact, lightweight
disintegrating head.

Straight shank arbor for drill press use.

Magnetic fixtures available.



**REMOVE
BROKEN TAPS
BOLTS & DRILLS
IN MINUTES**

PERFORMANCE

BROKEN TOOLING ONE INCH DEEP	REMOVAL TIME
0-80 to 10-32 No. 1.6	UNDER 1 min.
1/4" No. 6	1 - 2 min.
5/16" No. 8	1.5 - 2.5 min.
3/8" No. 10	1.5 - 2 min.
1/2" No. 14	2 - 4 min.
5/8" No. 18	1.5 - 2.5 min.
3/4" No. 22	2.5 - 3.5 min.



OPTIONAL Mini Mag Head Support Fixture

The ideal way to bring
disintegrating power to
bear at ANY angle.
800 lb.- force
permanent magnet.
6 precision angle/position
adjustments. 5" (127 mm)
vertical, 4.5" (114 mm)
horizontal movement.
4" (101 mm) of downfeed.
Part # A1425



MADE IN USA

Model X-2

SPECIFICATIONS

OPERATING HEAD	Operating head with 2.5" x 0.5" (63 x 13 mm) shank for chucking into machine shop tools. Vibrating head creates 120 cutting arcs per second.
POWER SUPPLY	Stainless steel cabinet 24" wide x 12.5" deep x 15.25" high (604 x 317 x 387 mm). Hinged locking cover. Fold-down handle on each end. Ten foot (3 m) 110 volt AC input cable. 30 amps required. Controls include start, stop, yellow ON indicator, heat selector with eleven selections, coolant on/off switch, vibration control, current meter and power overload circuit breaker. Receptacles for power, ground, pump and head vibration cables.
CABLES	Work Cable: Copper welding cable with jack plug. Head Cable: Copper welding cable with jack plug and encapsulated head vibration power cables. Both 10 ft (3 m).
COOLANT SYSTEM	Standalone coolant pump and motor (110 V AC). 1/3 HP pump provides 90 PSI to head from coolant tank or bucket (not included). Coolant can be recycled if provision is made to collect runoff from the workpiece. Two 10 ft (3 m) coolant hoses with quick disconnects.
SHIPPING DATA	Weight: Net 150 lb (68 kg), gross domestic 225 lb (102 kg). Volume: 8 cu ft (0.227 M)




OPTIONS

Build your complete mobile disintegration station



Accessory Basket

For head, cables, accessories. Rubber coated heavy wire construction. Part No. S-204



Cabling options

20 foot Power Cable	Part #S-220
20 foot Ground Cable	Part #S-221
Head Cord Extension 10 ft	Part #S-212

Coolant Tank

16-gallon durable frosted plastic resists corrosion. Built-in filter, barbed fitting for quick disconnect. Large screw-on fill cap with pressure relief valve. Fits perfectly on lower deck of the cart. Part No. S-203



Stainless Steel Cart

Welded joints and handle. Room below for coolant tank and extras. Heavy-duty lockable wheels; back pair are casters. Dimensions: 30" x 60" / (762 x 1524 mm) footprint. Height: 37" (939.8 mm) to top of handle, 27" (686 mm) to top shelf.

Part No. S-202

Coolant Valve

Offers dual coolant sources: tank or garden hose.

Part No. A6448



V1019

ELECTRO ARC MANUFACTURING COMPANY *STILLION INDUSTRIES*

USA

Phone: (734) 475-8527

Fax: (734) 475-2902

sales@electroarc.com

www.electroarc.com



UK

Phone +44 (0) 1384 231535

Fax: +44 (0) 1384 252834

sales@electroarc.co.uk